






BLAZE

ASH COLLECTION




PRODUCT INFORMATION

| | | |
|--|------------------------|-------------------------------|
|  | Species | European Ash |
|  | Surface texture | Smooth |
|  | Finish | Oil |
|  | Grades | Plank options: Rustic Dark |
|  | Construction | Duoplank® Engineered |


DIMENSIONS

| | | |
|--|----------------------|--|
|  | Thickness | 15, 20 mm (5/8", 3/4") |
|  | Plank widths | 80, 110, 142, 180, 240 mm (3 5/32", 4 11/32", 5 9/16", 7", 9 1/2") |
|  | Plank lengths | 1790, 1970, 2100, 2220, 2470 mm (5'11", 6'6", 6'11", 7'3", 8'1") |


INSTALLATION

| | | |
|--|--------------|---|
|  | Plank | Glue down, floating 4-side tongue & groove |
|--|--------------|---|

USAGE

| | | |
|--|--------------------------|---|
|  | Recommended usage | Suitable for use in all project sectors: Residential, Commercial, Hospitality, Retail |
|--|--------------------------|---|


SUBFLOOR HEATING & COOLING


| | | |
|--|----------------------|--|
|  | Compatibility | Guarantee available when installed and maintained in accordance with Hakwood Subfloor Heating & Cooling document |
|--|----------------------|--|


| SUSTAINABILITY | TEST METHOD | MINIMUM REQUIREMENT | PERFORMANCE |
|----------------------------|-------------|--|---------------------------------|
| FSC certified (Mix) | | FSC® Certificate-Code: SCS-COC-000609 | Meets requirement On request |

| ENGINEERED WOOD FLOORING STANDARD | TEST METHOD | MINIMUM REQUIREMENT | PERFORMANCE |
|---|-------------|---------------------|-------------------|
|  CE (Conformité Européenne) European standard | EN 14342 | CE Compliant | Meets requirement |

| LOW EMITTING MATERIALS | | TEST METHOD | MINIMUM REQUIREMENT | PERFORMANCE |
|--|--|---|-----------------------------|---------------------|
|  | E1 certificate | EN 717-7 | E1 compliant & E2 compliant | Meets requirement |
| | California Air Resources Board (CARB) Certificate for formaldehyde | ASTM E1333 | CARB Compliant | Meets requirement |
|  | Émissions dans l'air intérieur A+ label France national Volatile Organic Compound (VOC) A+ label | ISO 16000p 3,6,9 | | Testing in progress |
|  | AgBB German label for low emissions | ISO 16000 | | Testing in progress |
|  | CA 01350 California Section 01350 Test for VOC Emissions | CA DPHS Standard Practice Section 01350 | CA01350 Compliant | Testing in progress |

| SLIP RESISTANCE | | TEST METHOD | MINIMUM REQUIREMENT | PERFORMANCE |
|--|---|---|---------------------|---------------------|
|  | EN14342 Wood flooring - characteristics, evaluation of conformity and marking | CEN/TS 15676 Determination of the anti-skid properties | | Testing in progress |
| | | DIN 51130 | | Testing in progress |
| | | DIN 51097 / GUW-I 8527 | | Testing in progress |
| | | ASTM C1028-96 | | Testing in progress |

| SOUND TEST | | TEST METHOD | MINIMUM REQUIREMENT | PERFORMANCE |
|--|-------------------------------|------------------------------|---------------------|---------------------|
|  | Impact sound reduction | EN ISO 140-8 EN ISO 717-2 | | Testing in progress |

| SCRATCH RESISTANCE | | TEST METHOD | MINIMUM REQUIREMENT | PERFORMANCE |
|--|--|-------------|---------------------|---------------------|
|  | | DIN 68861 | | Testing in progress |

| REACTION TO FIRE | | TEST METHOD | MINIMUM REQUIREMENT | PERFORMANCE |
|--|---|----------------|---------------------|---------------------|
|  | EN14342 Wood flooring - characteristics, evaluation of conformity and marking | EN 13501-1 | | Testing in progress |
|  | Flame spread & smoke development | ASTM E84 | | Testing in progress |
| | | NFPA 101 | | Testing in progress |
| | | ASTM E648-10NY | | Testing in progress |

| | |
|---|--|
| Installation Information | Download the latest version at https://www.hakwood.com/en/downloads/ |
| Care & Maintenance Instruction | |
| Subfloor Heating & Cooling | |

Hakwood

Leemansstraat 2
4251LD Werkendam
the Netherlands
Tel: +31 183 504 266
sales@hakwood.com

Hakwood Inc.

2244 95th St, Suite 200
Naperville IL 60564
United States
Tel: +1 630 219 3388
ussales@hakwood.com

