

PRODUCT INFORMATION

	Species	European Ash
	Surface texture	Smooth
	Finish	Oil
	Grades	Plank options: Premier 1-bis Dark, Rustic Dark
	Construction	Duoplank® Engineered

DIMENSIONS

	Thickness	15, 20 mm (5/8", 3/4")
	Plank widths	80, 110, 142, 180, 240 mm (3 5/32", 4 11/32", 5 9/16", 7", 9 1/2")
	Plank lengths	1790, 1970, 2100, 2220, 2470 mm (5'11", 6'6", 6'11", 7'3", 8'1")

INSTALLATION

	Plank	Glue down, floating 4-side tongue & groove
--	--------------	---

USAGE

	Recommended usage	Suitable for use in all project sectors: Residential, Commercial, Hospitality, Retail
--	--------------------------	---


SUBFLOOR HEATING & COOLING


	Compatibility	Guarantee available when installed and maintained in accordance with Hakwood Subfloor Heating & Cooling document
--	----------------------	--


SUSTAINABILITY	TEST METHOD	MINIMUM REQUIREMENT	PERFORMANCE
FSC certified (Mix)		FSC® Certificate-Code: SCS-COC-000609	Meets requirement On request

ENGINEERED WOOD FLOORING STANDARD	TEST METHOD	MINIMUM REQUIREMENT	PERFORMANCE
CE (Conformité Européenne) European standard	EN 14342	CE Compliant	Meets requirement

LOW EMITTING MATERIALS		TEST METHOD	MINIMUM REQUIREMENT	PERFORMANCE
	E1 certificate	EN 717-7	E1 compliant & E2 compliant	Meets requirement
	California Air Resources Board (CARB) Certificate for formaldehyde	ASTM E1333	CARB Compliant	Meets requirement
	Émissions dans l'air intérieur A+ label France national Volatile Organic Compound (VOC) A+ label	ISO 16000p 3,6,9		Testing in progress
	AgBB German label for low emissions	ISO 16000		Testing in progress
	CA 01350 California Section 01350 Test for VOC Emissions	CA DPHS Standard Practice Section 01350	CA01350 Compliant	Testing in progress

SLIP RESISTANCE		TEST METHOD	MINIMUM REQUIREMENT	PERFORMANCE
	EN14342 Wood flooring - characteristics, evaluation of conformity and marking	CEN/TS 15676 Determination of the anti-skid properties		Testing in progress
		DIN 51130		Testing in progress
		DIN 51097 / GUW-I 8527		Testing in progress
		ASTM C1028-96		Testing in progress

SOUND TEST		TEST METHOD	MINIMUM REQUIREMENT	PERFORMANCE
	Impact sound reduction	EN ISO 140-8 EN ISO 717-2		Testing in progress

SCRATCH RESISTANCE		TEST METHOD	MINIMUM REQUIREMENT	PERFORMANCE
		DIN 68861		Testing in progress

REACTION TO FIRE		TEST METHOD	MINIMUM REQUIREMENT	PERFORMANCE
	EN14342 Wood flooring - characteristics, evaluation of conformity and marking	EN 13501-1		Testing in progress
	Flame spread & smoke development	ASTM E84		Testing in progress
		NFPA 101		Testing in progress
		ASTM E648-10NY		Testing in progress

Installation Information	Download the latest version at https://www.hakwood.com/en/downloads/
Care & Maintenance Instruction	
Subfloor Heating & Cooling	

Hakwood

Leemansstraat 2
4251LD Werkendam
the Netherlands
Tel: +31 183 504 266
sales@hakwood.com

Hakwood Inc.

2244 95th St, Suite 200
Naperville IL 60564
United States
Tel: +1 630 219 3388
ussales@hakwood.com

