

# Allure

LITE Collection



PRODUCT INFORMATION

|                                                                                   |                 |                                           |
|-----------------------------------------------------------------------------------|-----------------|-------------------------------------------|
|  | Species         | European Oak                              |
|  | Surface texture | Brushed                                   |
|  | Finish          | Oil                                       |
|  | Grades          | <b>Plank options:</b> Exclusive, Standard |
|  | Construction    | <b>Duoplank®</b><br>Engineered            |

DIMENSIONS

|                                                                                     |              |                                                                                                                                   |
|-------------------------------------------------------------------------------------|--------------|-----------------------------------------------------------------------------------------------------------------------------------|
|   | Thickness    | 14 mm ( 9/16")                                                                                                                    |
|  | Plank widths | 180 mm (7")                                                                                                                       |
|  | Plank length | 1080, 1220, 1470, 1790, 1970, 2100, 2190, 2220, 2400, 2470 mm (3'7", 4', 4'10", 5'11", 6'6", 6'11", 86 1/4", 7'3", 94 1/2", 8'1") |

INSTALLATION

|                                                                                     |                       |                                                                                           |
|-------------------------------------------------------------------------------------|-----------------------|-------------------------------------------------------------------------------------------|
|  | Plank                 | <b>Glue down</b><br>4-side tongue & groove                                                |
|                                                                                     | Herringbone & Chevron | <b>Glue down</b><br>1 side tongue, 2 side groove (Chevron includes left & right elements) |

USAGE

|                                                                                     |                   |                                                                                       |
|-------------------------------------------------------------------------------------|-------------------|---------------------------------------------------------------------------------------|
|  | Recommended usage | Suitable for use in all project sectors: Residential, Commercial, Hospitality, Retail |
|-------------------------------------------------------------------------------------|-------------------|---------------------------------------------------------------------------------------|

SUBFLOOR HEATING & COOLING

|                                                                                     |               |                                                                                                                  |
|-------------------------------------------------------------------------------------|---------------|------------------------------------------------------------------------------------------------------------------|
|  | Compatibility | Guarantee available when installed and maintained in accordance with Hakwood Subfloor Heating & Cooling document |
|-------------------------------------------------------------------------------------|---------------|------------------------------------------------------------------------------------------------------------------|

| SUSTAINABILITY                                                                                                                             | TEST METHOD      | MINIMUM REQUIREMENT                   |
|--------------------------------------------------------------------------------------------------------------------------------------------|------------------|---------------------------------------|
| <b>FSC certified (Mix)</b>                                                                                                                 |                  | FSC® Certificate-Code: SCS-COC-000609 |
| ENGINEERED WOOD FLOORING STANDARD                                                                                                          | TEST METHOD      | MINIMUM REQUIREMENT                   |
|  <b>CE (Conformité Européenne)</b><br>European standard | EN 14342         | CE Compliant                          |
| <b>NWFA (National Wood Flooring Association)</b><br>U.S. Standard                                                                          | ANSI/HPVA EF2009 | NWFA Compliant                        |

| LOW EMITTING MATERIALS                                                              |                                                                                                           | TEST METHOD                                                      | MINIMUM REQUIREMENT                                     |
|-------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------|------------------------------------------------------------------|---------------------------------------------------------|
|    | <b>E1 certificate</b>                                                                                     | EN 717-7                                                         | E1 compliant & E2 compliant                             |
|                                                                                     | <b>California Air Resources Board (CARB)</b><br>Certificate for formaldehyde                              | ASTM E1333                                                       | CARB 2 Compliant                                        |
|    | <b>Émissions dans l'air intérieur A+ label</b><br>France national Volatile Organic Compound(VOC) A+ label | ISO 16000p 3,6,9                                                 | Meets requirements                                      |
|    | <b>AgBB</b><br>German label for low emissions                                                             | ISO 16000                                                        | Meets requirement                                       |
|    | <b>CA 01350</b><br>California Section 01350 Test for VOC Emissions                                        | CA DPHS Standard Practice Section 01350                          | Meets requirements                                      |
| SLIP RESISTANCE                                                                     |                                                                                                           | TEST METHOD                                                      | MINIMUM REQUIREMENT                                     |
|    | <b>EN14342</b><br>Wood flooring - characteristics, evaluation of conformity and marking                   | <b>CEN/TS 15676</b><br>Determination of the anti-skid properties | <b>59 USRV USRV</b><br>Unpolished Slip Resistance Value |
|                                                                                     |                                                                                                           | DIN 51130                                                        | R9 (range 6°-10°)                                       |
|                                                                                     |                                                                                                           | DIN 51097 / GUV-I 8527                                           | B                                                       |
| SCRATCH RESISTANCE                                                                  |                                                                                                           | TEST METHOD                                                      | MINIMUM REQUIREMENT                                     |
|    |                                                                                                           | DIN 68861                                                        | 4E                                                      |
| REACTION TO FIRE                                                                    |                                                                                                           | TEST METHOD                                                      | MINIMUM REQUIREMENT                                     |
|  | <b>EN14342</b><br>Wood flooring - characteristics, evaluation of conformity and marking                   | EN 13501-1                                                       | Dfl-s1                                                  |
|  |                                                                                                           |                                                                  |                                                         |