

Bliss

LITE Collection



PRODUCT INFORMATION

	Species	European Oak
	Surface texture	Sawn
	Finish	Oil
	Grades	Plank options: Exclusive, Standard
	Construction	Duoplank® Engineered

DIMENSIONS

	Thickness	14 mm (9/16")
	Plank widths	180 mm (7")
	Plank length	1080, 1220, 1470, 1790, 1970, 2100, 2190, 2220, 2400, 2470 mm (3'7", 4', 4'10", 5'11", 6'6", 6'11", 86 1/4", 7'3", 94 1/2", 8'1")

INSTALLATION

	Plank	Glue down 4-side tongue & groove
	Herringbone & Chevron	Glue down 1 side tongue, 2 side groove (Chevron includes left & right elements)

USAGE

	Recommended usage	Suitable for use in all project sectors: Residential, Commercial, Hospitality, Retail
---	-------------------	---

SUBFLOOR HEATING & COOLING

	Compatibility	Guarantee available when installed and maintained in accordance with Hakwood Subfloor Heating & Cooling document
---	---------------	--

SUSTAINABILITY	TEST METHOD	MINIMUM REQUIREMENT
FSC certified (Mix)		FSC® Certificate-Code: SCS-COC-000609

ENGINEERED WOOD FLOORING STANDARD	TEST METHOD	MINIMUM REQUIREMENT
 CE (Conformité Européenne) European standard	EN 14342	CE Compliant
NWFA (National Wood Flooring Association) U.S. Standard	ANSI/HPVA EF2009	NWFA Compliant

LOW EMITTING MATERIALS		TEST METHOD	MINIMUM REQUIREMENT
	E1 certificate	EN 717-7	E1 compliant & E2 compliant
	California Air Resources Board (CARB) Certificate for formaldehyde	ASTM E1333	CARB 2 Compliant
	Émissions dans l'air intérieur A+ label France national Volatile Organic Compound(VOC) A+ label	ISO 16000p 3,6,9	Meets requirements
	AgBB German label for low emissions	ISO 16000	Meets requirement
	CA 01350 California Section 01350 Test for VOC Emissions	CA DPHS Standard Practice Section 01350	Meets requirements
SLIP RESISTANCE		TEST METHOD	MINIMUM REQUIREMENT
	EN14342 Wood flooring - characteristics, evaluation of conformity and marking	CEN/TS 15676 Determination of the anti-skid properties	Testing in progress USRV Unpolished Slip Resistance Value
		DIN 51130	Testing in progress
		DIN 51097 / GUV-I 8527	Testing in progress
SCRATCH RESISTANCE		TEST METHOD	MINIMUM REQUIREMENT
		DIN 68861	4E
REACTION TO FIRE		TEST METHOD	MINIMUM REQUIREMENT
	EN14342 Wood flooring - characteristics, evaluation of conformity and marking	EN 13501-1	Dfl-s1
			