






MONTGUYON

OLD WORLD COLLECTION

Hakwood










GREAT
FLOORING
STORIES







PRODUCT INFORMATION

| | | |
|---|------------------------|--|
|  SPECIES | Species | European Oak |
|  TEXTURE | Surface texture | Hand hewn |
|  FINISH | Finish | Oil |
|  GRADE | Grades | Plank options: Mixed Herringbone options: Mixed |
|  DUOPLANK | Construction | Duoplank® Engineered |

DIMENSIONS

| | | |
|--|---------------------|--|
|  THICKNESS | Thickness | 15 / 20 mm (5/8" / 3/4") |
|  WIDTH | Plank Width | 142 / 180 / 240mm (5 9/16" / 7" / 9 1/2") |
|  LENGTH | Plank Length | 1790 / 1970 / 2100 / 2220 / 2410 / 2470mm (5'11" / 6'6" / 6'11" / 7'3" / 8'1") |
|  PATTERN | Herringbone | 180 x 1080mm (7" x 42 1/2") |

| SUSTAINABILITY | | TEST METHOD | MINIMUM REQUIREMENT | PERFORMANCE |
|---|--|---|--|-----------------------------------|
|  | FSC certified (Mix) available on request | | FSC® Certificate Code: SCS-COC-000609 | Meets requirement upon request |
| EUROPEAN STANDARD | | TEST METHOD | MINIMUM REQUIREMENT | PERFORMANCE |
|  | CE Conformité Européenne | EN 14342 | CE Compliant | Meets requirement |
| LOW EMITTING MATERIALS | | TEST METHOD | MINIMUM REQUIREMENT | PERFORMANCE |
|  | E1 certificate European Formaldehyde label | EN 717-7 | E1 Compliant & E2 Compliant | Meets requirement |
|  | California Air Resources Board (CARB) Certificate for formaldehyde | ASTM E1333 | CARB Compliant | Meets requirement |
|  | Émissions dans l'air intérieur A+ label France national Volatile Organic Compound (VOC) A+ label | ISO 16000p 3,6,9 | A+ / very low-emission | Meets requirement |
|  | AgBB German label for low emissions | ISO 16000 | Meets requirement | Meets requirement |
|  | CA 01350 California Section 01350 Test for VOC Emissions | CA DPHS Standard Practice Section 01350 | CA01350 Compliant | Meets requirement |
| SLIP RESISTANCE | | TEST METHOD | MINIMUM REQUIREMENT | PERFORMANCE |
|  | EN14342 Wood flooring – characteristics, evaluation of conformity and marking | CEN/TS 15676 Determination of the anti- skid properties | 57 USRV Unpolished slip resistance value | Meets requirement |
| | | DIN 51130 | R10 (range 10-19) | Meets requirement |
| | | DIN 51097 / GUV-I 8527 | Class B | Meets requirement |
| | | ASTM C1028-96 | 0.62 (Dry) 0.61 (Wet) Static coefficient of friction | Meets requirement |
| SOUND TEST | | TEST METHOD | MINIMUM REQUIREMENT | PERFORMANCE |
|  | Impact sound reduction | EN 1533 | 20 mm:14 dB [ΔL_w] 15 mm:16 dB [ΔL_w] | Meets requirement |

| SCRATCH RESISTANCE | | TEST METHOD | MINIMUM REQUIREMENT | PERFORMANCE |
|---|---|---|---------------------|-------------------|
|  | | DIN 68861 | 4E | Meets requirement |
| REACTION TO FIRE | | TEST METHOD | MINIMUM REQUIREMENT | PERFORMANCE |
|  | EN14342 Wood flooring – characteristics, evaluation of conformity and marking | EN 13501-1 | Cfl-s1 | Meets requirement |
|  | Flame spread & smoke development | ASTM E84 | Class C | Meets requirement |
| | | NFPA 101 | Class C | Meets requirement |
| | | ASTM E648-10NY | Class II | Meets requirement |
| | NWFA National Wood Flooring Association (USA) | ANSI/HPVA EF2009 American national standard for engineered wood flooring | Meets requirement | Meets requirement |
| INSTALLATION | | | | |
|  | Plank | Glue down, floating 4-side tongue & groove | | |
| | Herringbone | Glue down 1 end tongue, 3 side groove. Necessary spline supplied. | | |
| USAGE | | | | |
|  | Recommended usage | Suitable for use in all project sectors: Residential, Commercial, Hospitality, Retail | | |
| UNDERFLOOR HEATING & COOLING | | | | |
|  | Compatibility | Guarantee available when installed and maintained in accordance with Hakwood Subfloor heating & Cooling document. | | |

Hakwood
Leemansstraat 2
4251 LD Werkendam
The Netherlands
Tel: +31 183 504 266
Fax: +31 183 504 652

Hakwood Inc.
55 South Main Street, Suite 355
Naperville, IL 60540
United States of America
Tel: +1 630 219 3388
Fax: +1 800 799 3166

Hakwood

GREAT
FLOORING
STORIES